

RUBCO COCONUTS INDIA (P) LIMITED

CIN:U51229KL2003PTC016068)

Regd.Office : Rubco House, South Bazar, Kannur-670 002, Kerala State, India

PH 91- 497 -2711134, 2709749, 2701908.

E-mail: info@rubcomail.com Web site: www.rubcogroup.com



Sl. No.	ITEM DESCRIPTION (5000 Nuts per Shift DC)	Qty.
1.	De shelling Cabin with Rigid Mild steel Structure Completely Dismantle Type to avail flexible assemblies and with Rubber sheet attached at the bottom point of the bin to avoid cracking of nuts while discharge from Conveyor, Chutes. Feeding of coconuts in bins is manual.	3 Sets
2.	De shelling Machine with 1 HP power rate with stainless steel Cover and rigid steel structure.	3 Sets
3.	Paring Machine double head with aluminum disk and hardened blade with stainless steel cover and rigid steel structure.	3 Sets
4.	White Meat Collection Belt Conveyor with rigid stainless steel structures and side guards, Non Toxic Food Grade Rubber Conveyor Belt 3 Ply (White) width: 0.6 Mtrs with 1HP motor power and starters.	1 No.
5.	Pre Storage Screw Conveyor (SS) for premier washing with 5 HP power rate, rigid stainless steel structure in product contact parts.	1 No.
6.	Screw Conveyor (SS) for premier washing for premier washing with 2 HP power rate, rigid stainless steel structure in product contact parts.	1 No.
7.	Meat Nut Pre Cutter (SS) with 1.5 HP power.	1 No.
8.	DC Cutter Feeding inclined Screw Conveyor with 1.5 HP power rate rigid steel frames with stainless steel guards.	1 No.
9.	DC Cutter (SS) Completely constructed with stainless steel material with standing provision with 1.5 HP power rate.	1 No.
10.	Dryer Feeding inclined Belt Conveyor with 1 HP power rate, rigid steel frames with stainless steel guards.	1 No.

11.	4X16 Ft. ESSAR combined Tray & Fluid Bed Dryer with complete requirements as per our standard design and specifications for DC Powder with Total 32 HP power rates without Dust Collection System. Working Temperature @ 90 to 100 ⁰ with Radiator without Boiler.	1 No.
12.	Steam Boiler with Steam Pipe Line Feed and Return and Valve and Feed Water Tank & Chimney 40 Ft. height.	1 No.
	VCO PROCESSING (SCREW EXPELLER)	
13.	Virgin Coconut Oil Cold Press Expeller with 15 to 20 Kg. per hour DCP input and 55 to 60% oil Extraction Capacity with 2 HP power rate.(SS 304) material contact parts	3 Nos.
14.	Filter Press With PP Plates along with rigid structure and pumps and flexible Pipes 1 HP +1 HP Power rate. 24 Inch plate 24 Nos. with SS Oil Collection Tray and flexible pipe line.	1 Set
15.	SS Storage Tanks Tanks for pre storage and final storage with Manhole provision, constructed with Stainless Steel material with standing legs - 500 Liters – 2 Nos. and 300 Liters – 2 Nos.	1 Set
16.	Dry Pulverizer Two Stage Coconut Flower (After expeller cake grinding) powder with 7.5 HP power rate, constructed with product contact parts are stainless steel. (SS 304)	1 Set
17	Warranty - The tenderer should give warranty to the machineries and accessories for the defects in material and working and also should offer maintenance support for a minimum period of three years of commissioning the unit.	
